



Klemmsan®

270354 T1-K

Multimode Timer With Trigger Input

General

Order Number	270 354
Casing Width (mm)	17,5
Connections	Screw Terminal
Functions	a, b, c, d, e, f, g, h, i, k
Type of Output	Two Relays
Adjustment of Timing-1 & Timing-2	—
Lux Adjustment Rate	—
Sensitivity Adjusement Rate	—
Supply Frequency	35-70 Hz
Trigger Input Voltage	24-300VAC/DC
Recovery Time	Maks. 100ms
Protection Class	IP20
Weight (g)	66
Mounting Type	Panel & Rail
Schematics	—
Dimensions	—

Auxiliary Contacts

Type	1 C/O (SPDT)
Max. Ratings - AC (for NO side)	5A/250V; 1250VA
Max. Ratings - DC (for NO side)	5A/30VDC; 150W
Mechanical Lifetime	≥ 10 ⁷ operations
Electrical Lifetime Operations (for NO side)	5x10 ⁴ (5A@250VAC) 1x 10 ⁵ (5A@30VDC)

Time Range

Timing-1	1s => 60s
----------	-----------

	Timing-2	—
Supply Voltage	DC	24-300VDC
	AC	24-300VAC
Ambient Conditions	Operating Temperature	-20 to + 60°C
	Storing Temperature	-40°C +75°C
	Relative Humidity (No Condensation)	Maks. 95%
Power Consumption	DC	<1.25W
	AC	<2.5VA
EMC-EMI	55011/A1, 61000-4-2, 61000-4-3/A1, 61000-4-4, 61000-4-5, 61000-4-6, 61000-4-8, 61000-4-11	✓
Liquid Level Electrode	Definition	—
	Order Number	—
	Packing Units	1

Avrupa standartlarına uygunluk belgesi - CE Certificate

UL Sertifikası - UL Certificate

Order
Info

270354 Multimode Timer With Trigger Input